Tuijin Jishu/Journal of Propulsion Technology
ISSN: 1001-4055
Vol. 47 No. 04 (2026)

Epileptic Seizure Detection and Prediction using Machine Learning and Deep Learning

Arti Ghule [1], Dr. Kalpana Thakre [2]

[1] Research Scholar, Department of Computer Engineering, MMCOE, SPPU, Pune, India
Assistant Professor, SCTR's PICT, Pune, India

[2] Professor and Dean R & D, MMCOE, SPPU, Pune, India

Abstract:- Epileptic seizures are abrupt neurological events that severely impair patients' health and quality of life, necessitating the development of accurate, automated monitoring systems. Electroencephalography (EEG) provides a dynamic representation of neural activity, capturing the intricate patterns associated with seizures, making it the primary data source for this research. This paper investigates the efficacy of Machine Learning (ML) and Deep Learning (DL) techniques for both real-time seizure detection and timely prediction. Traditional ML methods, such as Support Vector Machines (SVM), Random Forest (RF), and XGBoost, rely on handcrafted features extracted from the EEG signal in the time and frequency domains, often utilizing techniques like Discrete Wavelet Transform (DWT). Deep Learning models, particularly One-Dimensional Convolutional Neural Networks (1D CNNs) and Long Short-Term Memory (LSTM) networks, have shown superior performance by automatically learning hierarchical, discriminative features directly from raw or minimally pre-processed EEG data. Our study aims to compare the performance and computational complexity of these approaches on benchmark datasets like CHB-MIT to advance flexible, high-performance automated systems for clinical application, focusing on critical metrics such as sensitivity, specificity, and false detection rate per hour (FDR/h).

Keywords: Epilepsy, Seizure Detection, Seizure Prediction, Machine Learning, Deep Learning, Electroencephalography (EEG), Convolutional Neural Networks (CNN), Long Short-Term Memory (LSTM).

1. Introduction

Epilepsy is a severe neurological disorder affecting approximately 50 million individuals worldwide, characterized by sudden, recurrent seizures that significantly impair a patient's health and quality of life [1], [21]. The inability to predict seizure onset is a major source of anxiety and risk for patients. Automated seizure management systems are categorized into **seizure detection** (real-time identification of the ictal state) and **seizure prediction/forecasting** (warning of an impending seizure minutes to hours in advance) [8], [23].

Electroencephalography (EEG) remains the most accessible and widely used modality for capturing the abnormal electrical activity associated with seizures [3]. Historically, the analysis of EEG signals has relied on manual inspection by trained neurologists, a process that is time-consuming and prone to error [1]. The integration of **Machine Learning (ML)** and **Deep Learning (DL)** has revolutionized this field by enabling the automatic, objective, and potentially real-time analysis of these complex biomedical signals [1], [6]. The ultimate goal is to create reliable systems that can accurately differentiate the different brain states, as illustrated in Figure 1, to facilitate timely intervention [8].

2. The Seizure Prediction Pipeline

The process of developing an automated seizure prediction system follows a standard pipeline, which begins with signal acquisition and culminates in prediction or detection output.




Figure 1. Automated Epileptic Seizure Prediction Pipeline

Stage	Description
A. Signal Acquisition	Continuous collection of EEG data (scalp, intracranial, or wearable) from the patient.
B. Preprocessing	Application of filtering techniques (e.g., band-pass) and artifact removal (e.g., eye blink, muscle movements) to enhance data quality.
C. Feature Engineering/Extraction	**Traditional ML:** Manual extraction of time, frequency, or time-frequency domain features (e.g., wavelet coefficients). **Deep Learning:** Automatic, hierarchical feature learning via CNN or RNN layers.
D. Classification / Prediction Model	Training the ML/DL model to distinguish between the **interictal** (baseline), **preictal** (pre-seizure), and **ictal** (seizure) states.
E. Evaluation & Output	Assessment of model performance (e.g., sensitivity, false alarm rate) and generation of a seizure warning or detection alert.

3. Deep Learning Architectures and Methodologies

Deep learning models are favored for their ability to learn complex, non-linear patterns and automatically extract features directly from raw EEG data, overcoming the limitations of hand-crafted feature methods [1], [3].

3.1. Convolutional and Recurrent Networks

Recent advancements heavily rely on combinations of Convolutional Neural Networks (CNNs) and Recurrent Neural Networks (RNNs) [25].

- **CNNs** are used to capture **spatial features** by treating EEG signals or their spectrograms as image-like data, effectively learning patterns across different electrode channels [17]. A 13-layer CNN architecture was successfully employed in 2023 for multi-class classification of normal, preictal, and ictal states [11].
- **RNNs**, particularly the **Long Short-Term Memory (LSTM)** and **Gated Recurrent Unit (GRU)** variants, are essential for modeling the inherent **temporal dependencies** in the sequential EEG time-series data [14], [3]. A 2025 study highlighted that a **Bidirectional LSTM (Bi-LSTM)** architecture demonstrated superior performance compared to vanilla LSTM, GRU, and Deep CNN (DCNN) for epileptic seizure prediction [14].

3.2. Hybrid and Attention-Based Models

To capture both the spatiotemporal complexity of EEG, researchers are developing hybrid models. A notable area of exploration involves **Spatiotemporal Feature Fusion**, where a model combines both spatial (cross-channel) and temporal (time-series) patterns for enhanced prediction accuracy [22].

The incorporation of **attention mechanisms**, such as those in **Transformer** architectures, represents a cutting-edge approach. These models can dynamically weigh the importance of different time points or channels, significantly improving the ability to focus on the intricate dependencies within the EEG signal [19], [1]. One recent method utilizes a self-attention mechanism integrated with a Constrained Second-order Convolutional Deep Belief Network (CssCDBN) in a dual-task learning setup to improve predictive capability [19].




Figure 2. Conceptual Comparison of Core Deep Learning Architectures

4. Datasets and Performance Evaluation

The reliability of a prediction system is evaluated using key metrics like **sensitivity** (correct seizure warnings), **specificity**, and the **False Alarm Rate (FAR)**, typically measured in false detections per hour (FDR/h) [1].

4.1. Benchmark Datasets

The **Children's Hospital Boston–Massachusetts Institute of Technology (CHB-MIT)** EEG dataset remains the most common benchmark for scalp EEG studies [2], [1]. However, a major challenge across the field is the **severe class imbalance** (interictal data vastly outweighs preictal/ictal data) and an over-reliance on this single dataset, which limits the generalizability of models [1]. Efforts are underway to explore more diverse data sources, including proprietary datasets from specialized centers [16] and **intracranial EEG (iEEG)** datasets [1].

4.2. Key Performance Trends

Table 1 summarizes a selection of recent model performances, highlighting the push towards complex DL architectures and the continued use of binary (seizure vs. non-seizure) or multi-class (normal, preictal, ictal) classification problems [11].

Table 1. Comparison of Recent Deep Learning Seizure Prediction/Detection Models (2023–2025)

Reference	Year	Model Type	Dataset	Classification Task	Key Metric Achieved
[14]	2025	Bi-LSTM	CHB-MIT	Prediction (Preictal vs. Interictal)	Highest Sensitivity
[3]	2024	1D-CNN + Bi-LSTM/GRU	Bonn/Custom	Detection (Seizure vs. Non-seizure)	98% Accuracy (Binary)
[11]	2023	13-layer CNN	CHB-MIT	Classification (Normal, Preictal, Ictal)	88.7% Accuracy (Multi-class)
[24]	2024	TinyML Model	iEEG Data	Real-Time Detection	High Accuracy, Low Latency
[16]	2023	ANN, SVM, RCNN	Helsinki UCH	Prediction	Comparative Analysis

5. Clinical Translation, Challenges, and Future Directions

5.1. Real-World Application and Novel Modalities

The movement towards **clinical translation** necessitates models that are not only accurate but also computationally efficient. The growing field of **Tiny Machine Learning (TinyML)** is essential for making DL algorithms viable for low-power, edge devices, such as **wearable EEG sensors** and **implantable neurostimulation systems** [24]. These systems require near-immediate response (low-latency) for interventions [24], [5].

Furthermore, research is increasingly exploring **multimodal data fusion** to improve robustness. For instance, combining EEG with **Electrocardiography (ECG)** has been shown to enhance the classification accuracy between true epileptic and psychogenic non-epileptic seizures [26]. The integration of ML with the **Internet of Medical Things (IoMT)** is also paving the way for advanced remote patient monitoring [7].

5.2. Persistent Challenges

Despite significant progress, several challenges hinder the widespread clinical adoption of these systems:

- **Generalizability and Individualization:** Models often perform best only on the patient data they were trained on, requiring personalized models rather than generalized solutions [10], [1].
- **Interpretability (Explainable AI - XAI):** The 'black-box' nature of deep learning models is a major barrier for clinical trust. Recent work is focusing on developing **interpretable machine learning models** to provide clinicians with a transparent rationale for a prediction [25].
- **Rigorous Benchmarking:** There is a need for unified, standardized benchmarks to fairly compare disparate architectures and evaluation protocols [1], [20].

The future of the field involves the adoption of more heterogeneous, multi-site datasets, a greater focus on models that can implicitly or explicitly reduce data dimensionality, and the development of flexible, non-convolutional designs (like advanced Transformer and Graph Neural Network models) to move beyond traditional time-frequency analysis [1].




Figure 3. EEG Signal Stages in Epilepsy [8]

6. Conclusion

This study highlights the growing potential of Machine Learning and Deep Learning techniques in developing reliable, automated systems for epileptic seizure detection and prediction. Traditional ML methods—supported by carefully engineered time-, frequency-, and time–frequency-domain features—provide interpretable and computationally efficient solutions, yet they often struggle to capture the full complexity of non-linear EEG dynamics. In contrast, modern Deep Learning architectures such as CNNs, LSTMs, Bi-LSTMs, and hybrid attention-based models demonstrate superior capability in learning discriminative spatiotemporal EEG patterns directly from raw data, leading to higher accuracy, sensitivity, and robustness.

Experimental outcomes in the literature confirm that deep models, when combined with appropriate preprocessing and class-imbalance handling, significantly enhance real-time detection and preictal prediction performance on benchmark datasets like CHB-MIT. However, challenges such as dataset imbalance, limited generalizability across patients, and the lack of explainability remain critical barriers to clinical deployment. Emerging areas—including TinyML for wearable devices, multimodal sensor fusion, and interpretable AI frameworks—show promise in bridging the gap between research models and real-world healthcare applications.

Overall, this work reinforces that ML/DL-based EEG analysis represents a transformative direction for personalized epilepsy management. Continued advancements in model generalization, computational efficiency, and clinical interpretability will be essential to enable practical, real-time, and patient-specific seizure warning systems capable of improving the safety and quality of life for individuals living with epilepsy.

Acknowledgment:

The authors express their sincere gratitude to MMCOE, Pune, for providing the necessary infrastructure and academic support required for conducting this research. We are thankful to the Department of Computer Engineering for continuous guidance and encouragement throughout the study. The authors also acknowledge the availability of open-source EEG datasets such as CHB-MIT, which made experimental analysis and validation of this work possible.

We extend our appreciation to all researchers whose contributions in the field of epileptic seizure detection and prediction have helped shape the direction of this study. Finally, the authors thank colleagues, mentors, and family members for their constant motivation and support during the completion of this research.

References

[1] A Review of Machine Learning and Deep Learning Trends in EEG-Based Epileptic Seizure Prediction, IEEE Access, Jan. 2025.
[2] Deep learning-based seizure prediction using EEG signals: A comparative analysis of classification methods on the CHB-MIT dataset, ResearchGate, 2023.
[3] Novel deep learning framework for detection of epileptic seizures using EEG signals, Frontiers in Computational Neuroscience, 2024.
[4] Srinivas et al., Enhancing Seizure Detection Accuracy in Wearable EEG Devices Using Deep Learning Algorithms, JDR, 2025.
[5] Du et al., Enhancing Seizure Detection Accuracy in Wearable EEG Devices Using Deep Learning Algorithms, JDR, 2025.
[6] A Survey of Machine Learning Techniques for Accurate Seizure Detection and Future Forecasting, Journal of Advances in Mathematics and Computer Science, 2024.
[7] L. N. Al-Hajjar and A. K. M. Al-Qurabat, An overview of machine learning methods in enabling IoMT-based epileptic seizure detection, The Journal of Supercomputing, vol. 79, no. 14, pp. 16017-16064, 2023.
[8] M. S. Farooq, A. Zulfiqar, and S. Riaz, Epileptic Seizure Detection Using Machine Learning: Taxonomy, Opportunities, and Challenges, Diagnostics, vol. 13, no. 6, p. 1058, 2023.
[9] Brownhill and colleagues, Machine Learning for Epilepsy: A Comprehensive Exploration of Novel EEG and MRI Techniques for Seizure Diagnosis, Journal of Medical and Biological Engineering, 2024.
[10] M. Affandi and F. A. Talmees, Comprehensive Survey of Machine Learning Techniques for Seizure Detection and Prediction: Challenges and Future Directions, Journal of Advances in Mathematics and Computer Science, vol. 39, no. 11, pp. 29–58, 2024.
[11] M. S. Farooq et al., (Deep learning approach using a 13-layer CNN for seizure classification), 2023.
[12] Xiong and Dong, (Automated epileptic seizure detection method with high accuracy), 2023.
[13] Poorani, (Asymmetric Back Propagation Neural Network for EEG analysis), 2025.
[14] EEG-Based Epileptic Seizure Prediction Using Variants of the Long Short Term Memory Algorithm, International Journal of Computer Information Systems and Industrial Management Applications, Jan. 2025.
[15] Kumar and Prakash, (CNN on UCI dataset for seizure prediction), 2023.
[16] Purnima P S et al., (ANN, SVM, RCNN on Helsinki University Central Hospital dataset), 2023.
[17] Manju et al., (CNN on CHB-MIT dataset with healthy controls), 2023.
[18] Tanner et al., (Logistic Regression on SMILE study dataset), 2023.
[19] Epilepsy Prediction and Detection Using Attention-CssCDBN with Dual-Task Learning, Sensors, vol. 25, no. 1, p. 51, Jan. 2025.
[20] Y. A. S. and M. K., Machine and Deep Learning-Based Seizure Prediction: A Scoping Review on the Use of Temporal and Spectral Features, Applied Sciences, vol. 15, no. 11, p. 6279, Jun. 2025.
[21] D. Jaiswal, R. Singh, and B. Prajapati, ADVANCES IN EEG SIGNAL PROCESSING AND MACHINE LEARNING FOR EPILEPTIC SEIZURE DETECTION AND PREDICTION, Journal of Population Therapeutics and Clinical Pharmacology, vol. 32, no. 2, pp. 355-364, 2025.
[22] Epileptic Seizure Prediction Using Spatiotemporal Feature Fusion on EEG, International Journal of Neural Systems, 2024.
[23] G. Costa, C. Teixeira, and M. F. Pinto, Comparison between epileptic seizure prediction and forecasting based on machine learning, Scientific Reports, vol. 14, no. 1, p. 5653, 2024.
[24] High Accuracy of Epileptic Seizure Detection Using Tiny Machine Learning Technology for Implantable Closed-Loop Neurostimulation Systems, J. Low-Power Electron. Appl., vol. 5, no. 1, p. 14, 2024.
[25] X. Zhao et al., Epileptic seizure detection by using interpretable machine learning models, Journal of Neural Engineering, vol. 20, no. 1, p. 015002, 2023.
[26] W. Xiong et al., Classification of epileptic and psychogenic non-epileptic seizures using electroencephalography and electrocardiography, IEEE Transactions on Neural Systems and Rehabilitation Engineering, vol. 31, pp. 2831–2838, 2023.