

# Super fibonacci graceful anti – magic labeling for flower graphs and python coding

<sup>[1]</sup>D. Amuthavalli, <sup>[2]</sup>O. V. Shanmuga Sundaram

<sup>[1]</sup> Research scholar, department of mathematics, sree saraswathi thyagaraja college, pollachi.

<sup>[2]</sup> Associate professor, department of mathematics, sree saraswathi thyagaraja college, pollachi.

Email id: <sup>[1]</sup>dpamuthavalli1@gmail.com, <sup>[2]</sup>ovs3662@gmail.com

## Abstract:

A graph  $G = (V, E, \phi)$  with  $p$  vertices and  $q$  edges. A super fibonacci graceful anti-magic labeling [SFGAML] of  $G$  is an injective function  $\phi: V \rightarrow \{0, F_2, F_3, \dots, F_{q+1}\}$  such that the induced edge labeling  $\phi^*(uv) = |\phi(u) - \phi(v)|$  is a bijection onto the set  $\{F_2, F_3, F_4, \dots, F_{q+1}\}$ . In addition, all the vertex sums are pairwise distinct and all the edges are unique. If a graph  $G$  admits a super fibonacci graceful anti magic labeling [SFGAML] then  $G$  is called super fibonacci graceful anti- magic graph [SFGAMG]. In this article the concept of super fibonacci graceful anti- magic labeling [SFGAML] is introduced and investigated with some flower graphs. These graphs are called super fibonacci graceful anti magic graph [SFGAMG].

**Msc classification:** 05c76, 05c78

**Keywords:** clematis flower graph, cherry blossom flower, rose flower, SFGAML, SFGAMG.

## 1. Introduction

Fibonacci graceful labeling idea was introduced by E. Barkaukas et. all [3]. Hartsfield and Ringel introduced the concept of Anti-Magic labeling. The concept of Fibonacci Anti-magic labeling was introduced by Ameenabibi and T. Ranjani [1]. A. Rosa [12] has Published “vertex values of a graph”. It is the beginning of vertex labeling. Wang [13] shows that the Cartesian products of the cycles are Anti-Magic. In nature many plants having the number of petals in Fibonacci series like lilies and buttercups. Now this article is based on connected, undirected and Flower Graphs. Python is the most popular language across worldwide. It was introduced by GuioVan Rossum on February 20,1991. Super Fibonacci Graceful Anti- Magic Labeling [SFGAML]concept is introduced here. While investigating, some Flower graphs are Super Fibonacci Graceful Anti Magic Graph [SFGAMG].Here Python coding is generated for the Super Fibonacci Graceful Anti-Magic Labeling for some Flower graphs. Here Cherry blossom flower graph, Clematis flower graph and Rose flower graphs are introduced and we also proved the graphs are SFGAMG.

## 2. Definitions

**Definition 2.1:** The Fibonacci numbers  $F_1, F_2, F_3, \dots$  are defined by  $F_0 = 0, F_1 = 1, F_2 = 1, \dots$  and  $F_{n+1} = F_n + F_{n-1}, n \geq 1$ . The Fibonacci sequence is 1,1,2,3,5 ...

**Definition 2.2:** A Super Fibonacci Graceful Anti-magic labeling [SFGAML] of  $G$  is an injective function  $\phi: V \rightarrow \{0, F_2, F_3, \dots, F_{q+1}\}$  such that the induced edge labeling  $\phi^*(uv) = |\phi(u) - \phi(v)|$  is a bijection onto the set  $\{F_2, F_3, F_4, \dots, F_{q+1}\}$ . In addition, all the vertex sums are pairwise distinct and all the edges are unique. If a graph  $G$  admits a Super Fibonacci Graceful Anti magic labeling [SFGAML] then  $G$  is called Super Fibonacci Graceful Anti- Magic Graph [SFGAMG].

**Definition 2.3:** A shell graph is Cycle  $C_{n+1}$  with  $(n - 2)$  chords sharing a common end vertex. It is denoted by  $C[n + 1, n - 2]$ .

**Definition 2.4:** A Clematis Flower graph  $C_{n,m}$  is obtained by joining  $n$  copies of  $C_4 + e$  and  $m$  copies  $K_2$  with a common vertex.

**Definition 2.5:** A Cherry Blossom Flower graph  $CB_{n,m}$  is obtained by joining  $n$  copies of the cycle  $C_3$  and  $m$  copies  $K_2$  with a common vertex.

**Definition 2.6:** A Rose flower graph  $R_n$  is obtained by joining  $n$  copies of the cycle  $C_6$  with a common vertex.

**Definition 2.7:** The Vertex sum at one vertex is the sum of labels of edges. These edges are incident to that vertex.

### 3. Results

#### 3.1. Theorem

Clematis Flower graph  $C_{nm}$  is *SFGAMG* for all  $n$ .

Proof :

Let  $C_{nm}$  be the Clematis Flower graph. The order of  $C_{nm}$  is  $p = 3n + m + 1$  and the size  $q = 5n + m$ . Let  $V(G) = \{a_0, a_1, a_2, \dots, a_m, b_1, b_2, \dots, b_n, c_1, c_2, \dots, c_n, d_1, d_2, \dots, d_n\}$  be the vertex set. Let  $a_0$  be the central vertex,  $b_1, b_2, \dots, b_n$  be the second vertices of  $C_4 + e$ ,  $c_1, c_2, \dots, c_n$  be the third vertices of  $C_4 + e$ ,  $d_1, d_2, \dots, d_n$  be the fourth vertices of  $C_4 + e$  and  $a_1, a_2, \dots, a_m$  be the pendent vertices. The edge set  $E(G) = \{e_j, e_{ii}, e_{oi}, s_{ii}, p_{oi}\}$  here  $e_j = (a_0, a_j)$ ,  $e_{ii} = (b_i c_i)$ ,  $e_{oi} = (a_0 b_i)$ ,  $s_{ii} = (c_i d_i)$ , and  $s_{oi} = (a_0 d_i)$

Define  $\phi: V \rightarrow \{0, F_1, F_2, \dots, F_{q+1}\}$

$$\phi(a_0) = 0$$

$$\phi(a_j) = F_{j+1} \quad \text{for } j = 1, 2, 3, \dots, m \quad m = \text{No. of Pendant Vertices}$$

$$\phi(b_i) = F_{m+5i-3} \quad \text{for } i = 1, 2, 3, \dots, n \quad n = \text{No. of Copies of } C_4 + e$$

$$\phi(c_i) = F_{m+5i-1} \quad \text{for } i = 1, 2, 3, \dots, n$$

$$\phi(d_i) = F_{m+5i+1} \quad \text{for } i = 1, 2, 3, \dots, n$$

The edge labels are

$$e_j = \phi^*(a_0 a_j) = |\phi(a_0) - \phi(a_j)| \quad \text{for } j = 1, 2, 3, \dots, m$$

$$e_{ii} = \phi^*(b_i c_i) = |\phi(b_i) - \phi(c_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$e_{oi} = \phi^*(a_0 b_i) = |\phi(a_0) - \phi(b_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$s_{ii} = \phi^*(c_i d_i) = |\phi(c_i) - \phi(d_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$s_{oi} = \phi^*(a_0 d_i) = |\phi(a_0) - \phi(d_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

Here all the vertex sums are pairwise distinct and all the edges are unique.

Thus  $\phi$  admits *SFGAML*.

Hence Clematis Flower graph  $C_{nm}$  is *SFGAMG*.

Python coding and output is enclosed in the Appendix.

#### Example 3.1




Fig 1: Clematis Flower graph  $C_{35}$  is *SFGAMG*

### 3.2. Theorem

Cherry Blossom Flower graph  $CB_{nm}$  is *SFGAMG* for all  $n$ .

Proof :

Let  $CB_{nm}$  be the Cherry Blossom Flower graph. The order of  $CB_{nm}$  is  $p = 2n + m + 1$  and the size  $q = 3n + m$ . Let  $V(G) = \{a_0, a_1, a_2, \dots, a_n, b_1, b_2, \dots, b_n, c_1, c_2, \dots, c_m\}$  be the vertex set. Let  $a_0$  be the central vertex,  $a_1, a_2, \dots, a_n$  be the second vertices of the cycle  $C_3$ ,  $b_1, b_2, \dots, b_n$  be the third vertices of the cycle  $C_3$  and  $c_1, c_2, \dots, c_m$  be the pendent vertices. The edge set  $E(G) = \{e_i, e_{ii}, e_j\}$  here  $e_i = (a_0, a_i)$ ,  $e_{ii} = (a_i b_i)$  and  $e_j = (a_0 c_j)$

Define  $\phi: V \rightarrow \{0, F_1, F_2, \dots, F_{q+1}\}$

$$\phi(a_0) = 0$$

$$\phi(a_i) = F_{3i} \quad \text{for } i = 1, 2, 3, \dots, n \quad n = \text{No. of Copies of cycle } C_3$$

$$\phi(b_i) = F_{3i+1} \quad \text{for } i = 1, 2, 3, \dots, n$$

$$\phi(c_j) = F_{3n+1+j} \quad \text{for } j = 1, 2, 3, \dots, m \quad m = \text{No. of Pendant Vertices}$$

The edge labels are

$$e_i = \phi^*(a_0 a_i) = |\phi(a_0) - \phi(a_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$e_{ii} = \phi^*(a_i b_i) = |\phi(a_i) - \phi(b_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$e_j = \phi^*(a_0 c_j) = |\phi(a_0) - \phi(c_j)| \quad \text{for } j = 1, 2, 3, \dots, m.$$

Here all the vertex sums are pairwise distinct and all the edges are unique.

Thus  $\phi$  admits *SFGAML*.

Hence the Cherry Blossom Flower graph  $CB_{nm}$  is *SFGAMG*.

Python coding and output is enclosed in the Appendix.

#### Example 3.2




Fig 2: Cherry Blossom Flower graph  $CB_{4,3}$

### 3.3. Theorem

Rose flower graph  $R_n$  is *SFGAMG* for all  $n$ .

Proof:

Let  $R_n$  be Rose flower graph. The order of the Rose flower graph  $R_n$  is  $p = 6n$  and size is  $q = 6n$ . The vertex set  $V(G) = \{a_0, a_1, a_2, \dots, a_n, b_1, b_2, \dots, b_n, c_1, c_2, \dots, c_n, d_1, d_2, \dots, d_n, e_1, e_2, \dots, e_n\}$ . Let  $a_0$  be the central vertex,  $a_1, a_2, \dots, a_n$  be the second vertices of the cycle  $C_6$ ,  $b_1, b_2, \dots, b_n$  be the third vertices of the cycle  $C_6$ ,  $c_1, c_2, \dots, c_n$  be the fourth vertices of the cycle  $C_6$ ,  $d_1, d_2, \dots, d_n$  be the fifth vertices of the cycle  $C_6$  and  $e_1, e_2, \dots, e_n$  be the sixth vertices of the cycle  $C_6$ .

$E(G) = \{u_i, v_i, w_i, x_i, y_i, z_i\}$  here  $u_i = \{a_0 a_i\}$ ,  $v_i = \{a_i b_i\}$ ,  $w_i = \{b_i c_i\}$ ,  $x_i = \{c_i d_i\}$ ,  $y_i = \{d_i e_i\}$ ,  $z_i = \{a_0 e_i\}$ .

Define  $\phi: V \rightarrow \{0, F_1, F_2, \dots, F_{q+1}\}$

$$\phi(a_0) = 0$$

$$\phi(a_i) = F_{6i+1} \quad \text{for } i = 1, 2, \dots, n$$

$$\phi(b_i) = F_{6i-1} \quad \text{for } i = 1, 2, \dots, n$$

$$\phi(c_i) = F_{6i} \quad \text{for } i = 1, 2, \dots, n$$

$$\phi(d_i) = F_{6i-2} \quad \text{for } i = 1, 2, \dots, n$$

$$\phi(e_i) = F_{6i-4} \quad \text{for } i = 1, 2, \dots, n$$

The edge labels are

$$u_i = \phi^*(a_0 a_i) = |\phi(a_0) - \phi(a_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$v_i = \phi^*(a_i b_i) = |\phi(a_i) - \phi(b_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$w_i = \phi^*(b_i c_i) = |\phi(b_i) - \phi(c_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$x_i = \phi^*(c_i d_i) = |\phi(c_i) - \phi(d_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

$$y_i = \phi^*(d_i e_i) = |\phi(d_i) - \phi(e_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$


$$z_i = \phi^*(a_0 e_i) = |\phi(a_0) - \phi(e_i)| \quad \text{for } i = 1, 2, 3, \dots, n$$

Here all the vertex sums are pairwise distinct and all the edges are unique.

Thus  $\phi$  admits *SFGAML*. Hence the graph  $R_n$  is *SFGAMG*.

Python coding and output is enclosed in the Appendix.

**Example 3.3**



**Fig 3:** Rose flower graph  $R_4$  is *SFGAMG*

**3. Conclusion:**

In this article the concept of Super Fibonacci Graceful Anti-Magic Labeling is introduced and explained. The Flower graphs demonstrated and proved that they are Super Fibonacci Graceful Anti – Magic Graphs. Python coding is generated for all functions in Flower graphs and also for Super Fibonacci Graceful Anti-Magic Labeling. Thus the real life Flowers are represented in Super Fibonacci Graceful Anti-Magic Graphs. In future different concept of labeling can also be developed.

APPENDIX:

1. Python Coding and output for Clematis Flower graph  $C_{nm}$ .

```

1 n=int(input("Enter the n Value: "))
2 m=int(input("Enter the m Value: "))
3 subscript = str.maketrans("0123456789", "0123456789")
4
5 print(f"φ(a0) = 0".translate(subscript))
6
7
8 for i in range(n):
9     i+=1
10    for j in range(m):
11        j+=1
12        a=j+1
13        b=((m+(5*i))-3)
14        c=((m+(5 * i))-1)
15        d=((m+(5*i))+1)
16        print(f"φ(a{j}) = F{a}".translate(subscript))
17        print(f"φ(b{i}) = F{b}".translate(subscript))
18        print(f"φ(c{i}) = F{c}".translate(subscript))
19        print(f"φ(d{i}) = F{d}".translate(subscript))
20
21    print("")
22
23
    
```

Output:

```

Enter the n Value: 3
Enter the m Value: 3
φ(a0) = 0
φ(a1) = F2
φ(b1) = F5
φ(c1) = F7
φ(d1) = F9

φ(a2) = F3
φ(b2) = F5
φ(c2) = F7
φ(d2) = F9

φ(a3) = F4
φ(b3) = F5
φ(c3) = F7
φ(d3) = F9

φ(a1) = F2
φ(b2) = F10
φ(c2) = F12
φ(d2) = F14

φ(a2) = F3
φ(b2) = F10
φ(c2) = F12
φ(d2) = F14

φ(a3) = F4
φ(b3) = F10
    
```

2. Python Coding and output for Cherry Blossom Flower graph  $CB_{nm}$ .

```

n=int(input("Enter the n Value: "))
m=int(input("Enter the m Value: "))
subscript = str.maketrans("0123456789", "0123456789")

print(f"φ(a0) = 0".translate(subscript))

for i in range(n):
    i+=1
    for j in range(m):
        j+=1
        print(f"φ(a{i}) = F{3*i}".translate(subscript))
        print(f"φ(b{i}) = F{3*i+1}".translate(subscript))
        print(f"φ(c{j}) = F{3*n+1+j}".translate(subscript))

    print("")
    
```

Output:

```

Enter the n Value: 2
Enter the m Value: 2
φ(a0) = 0
φ(a1) = F3
φ(b1) = F4
φ(c1) = F6

φ(a1) = F3
φ(b1) = F4
φ(c2) = F6

φ(a2) = F6
φ(b2) = F7
φ(c1) = F6

φ(a2) = F6
φ(b2) = F7
φ(c2) = F6
    
```

### 3. Python Coding and output for Rose Flower graph $R_n$ .

```

Untitled0.ipynb
File Edit View Insert Runtime Tools Help All changes saved
Press F11 to exit full screen
+ Code + Text
n=int(input("Enter the n Value: "))
subscript = str.maketrans("0123456789", "0123456789")

print(f"φ(a{0}) = 0".translate(subscript))

for i in range(n):
    i+=1
    print(f"φ(a{i}) = F{6*i+1}".translate(subscript))
    print(f"φ(b{i}) = F{6*i-1}".translate(subscript))
    print(f"φ(b{i}) = F{6*i-2}".translate(subscript))
    print(f"φ(b{i}) = F{6*i-4}".translate(subscript))
    print(f"φ(b{i}) = F{6*i}".translate(subscript))
    print("")

Enter the n Value: 2
φ(a0) = 0
φ(a1) = F1
φ(b1) = F2
φ(b1) = F4
φ(b1) = F2
φ(b1) = F6

φ(a2) = F13
φ(b2) = F11
φ(b2) = F10
φ(b2) = F8
φ(b2) = F12
    
```

3s completed at 10:35AM

### References

- [1] Ameenal Bibi.K and T. Ranjani "Fibonacci mean Anti-magic labeling of some graphs" Kong.Res.J. ISSN: 2349-2694
- [2] Bondy J. A. and Murty U.S. R., Graph Theory with applications, Newyork Macmill Ltd. Press (1976).
- [3] David.W and Anthony.E. Barakaukas, "Fibonacci graceful graphs".
- [4] D. Amuthavalli and M. Sangeetha "Super Fibonacci Gracefulness of shell related graphs". International Journal of Mathematics Trends and Technology volume 53-No.6.January 2018.
- [5] D. Amuthavalli and M. Premkumar "Super Fibonacci Graceful labeling of cycle related graphs". International Journal of Mathematics Trends and Technology volume 38-No.3.October 2016.
- [6] Joseph A. Gallian, "A Dynamic survey of graph labeling", the electronic journal of combinatorics, (2022).
- [7] Tao-Ming wang and Cheng-Chih Hsiao "On anti-magic labeling for graphs products", the ScienceDirect, Discrete Mathematics 308(2008) 3624-3633.
- [8] Sivaranjani.B and R. Kala "Fibonacci mean Anti-magic labeling of some graphs" Advances in Mathematics: Scientific Journal 9 (2020), no.5 2561-2572.ISSN: 1857-8365.
- [9] Solomon Golomb "Graph Theory and Computing" (Academic Press: 1972).
- [10] S. Somasundaram & T. Nicholas "on (ad) -anti magic special trees, unicyclic graphs and complete bipartite graphs ars.com, 70,2004 207-220.
- [11] Stewart .B.M , Magic graphs , Canad.J.18 (1966) 1031-1059.
- [12] Rosa .A " On certain Valuation of vertices of graph", (1967).
- [13] Wang .T Toroidal grids are anti-magic , Lecture notes in Computer Science , Vol 3595,pp.671-679.